



	<b>Expansievatconsole</b>	<b>Expansievatconsole</b>
	<b>3-gats</b>	<b>4-gats</b>
	<b>Diverse kleuren</b>	<b>Diverse kleuren</b>
<b>Materiaal</b>	Q235 Staal	Q235 Staal
<b>Kleur</b>	Rood/Wit/Grijs/Zilverwit	Rood/Wit/Grijs
<b>Max. werktemperatuur</b>	90 °C	90 °C
<b>Max. werkdruk</b>	10 bar	10 bar
<b>Mogelijke meeruitvoering</b>	Incl. Puntstuk en Ontluchter	Incl. Puntstuk en Ontluchter
<b>Aansluiting 1</b>	G 1/2" BI	G 1/2" BI
<b>Aansluiting 2</b>	G 3/4" BI	G 3/4" BI
<b>Aansluiting 3</b>	G 1/2" BI	G 1/2" BI
<b>Aansluiting 4</b>	N.V.T.	G 1/2" BI
<b>Bevestigingsmethode</b>	Sleufgaten max. 8 mm	Sleufgaten max. 8 mm
<b>Totale gewicht</b>	710 gram	700 gram
<b>Totale lengte</b>	280 mm	280 mm
<b>Totale breedte</b>	55 mm	55 mm
<b>Totale hoogte</b>	110 mm	110 mm
	<b>Expansion Tank Console</b>	<b>Expansion Tank Console</b>
	<b>3-hole</b>	<b>4-hole</b>
	<b>Various colours</b>	<b>Various colours</b>
<b>Material</b>	Q235 Steel	Q235 Steel
<b>Colour</b>	Red/White/Grey/Silvery-white	Red/White/Grey
<b>Max. working temperature</b>	90 °C	90 °C
<b>Max. working pressure</b>	10 bar	10 bar
<b>Possible addition</b>	Incl. Coupling and Vent	Incl. Coupling and Vent
<b>Connection 1</b>	G 1/2" F	G 1/2" F
<b>Connection 2</b>	G 3/4" F	G 3/4" F
<b>Connection 3</b>	G 1/2" F	G 1/2" F
<b>Connection 4</b>	N/A	G 1/2" F
<b>Fastening method</b>	Slotted holes max. 8 mm	Slotted holes max. 8 mm
<b>Total weight</b>	710 gram	700 gram
<b>Total length</b>	280 mm	280 mm
<b>Total width</b>	55 mm	55 mm
<b>Total height</b>	110 mm	110 mm