



	Gasaansluitkraan	Gasaansluitkraan
	RECHT met Vlindergreep	HAAKS met Vlindergreep
	1/2"xM24 BU	1/2"xM24 BU
Materiaal	CW617N	CW617N
Kleur	Zilverwit	Zilverwit
Oppervlaktebehandeling	Vernikkeld (Gezandstraald)	Vernikkeld (Gezandstraald)
Min./max. werktemperatuur	-5/70 °C	-5/70 °C
Max. werkdruk	0.2 bar	0.2 bar
Aansluiting 1	G 1/2" BU	G 1/2" BU
Aansluiting 2	M24 BU	M24 BU
Bevestigingsmethode	22 mm Steeksleutel	22 mm Steeksleutel
Doorlaat	10 mm (gereduceerde doorlaat)	10 mm (gereduceerde doorlaat)
Totale gewicht	149 gram	158 gram
Totale lengte	67 mm	45 mm
Totale breedte	32 mm	32 mm
Totale hoogte	52 mm	86 mm
	Gas Connection Valve	Gas Connection Valve
	STRAIGHT with Butterfly grip	ANGLED with Butterfly grip
	1/2"xM24 M	1/2"xM24 M
Material	CW617N	CW617N
Colour	Silvery-white	Silvery-white
Surface finish	Nickel Plated (Sandblasted)	Nickel Plated (Sandblasted)
Min./max. working temperature	-5/70 °C	-5/70 °C
Max. working pressure	0.2 bar	0.2 bar
Connection 1	G 1/2" M	G 1/2" M
Connection 2	M24 M	M24 M
Fastening method	22 mm Wrench	22 mm Wrench
Bore	10 mm (reduced bore)	10 mm (reduced bore)
Total weight	149 gram	158 gram
Total length	67 mm	45 mm
Total width	32 mm	32 mm
Total height	52 mm	86 mm