



	Vulslang	Vulslang	Vulslang	Vulslang
	BASIC Blauw incl. ontl.sl.	BASIC Blauw incl. ontl.sl.	BASIC Blauw incl. ontl.sl.	BASIC Rood incl. ontl.sl.
	150 cm 3/4" BI	350 cm 3/4" BI	500 cm 3/4" BI	500 cm 3/4" BI
Materiaal van de Slang	PVC	PVC	PVC	PVC
Materiaal van de Koppeling	POM	POM	POM	POM
Kleur van de Slang	Blauw	Blauw	Blauw	Rood
Kleur van de Koppeling	Wit	Wit	Wit	Wit
Max. werktemperatuur	25 °C	25 °C	25 °C	25 °C
Max. werkdruk	10 bar	10 bar	10 bar	10 bar
Inbegrepen accessoire	Ontluchtings sleutel	Ontluchtings sleutel	Ontluchtings sleutel	Ontluchtings sleutel
Aansluiting 1	G 3/4" BI	G 3/4" BI	G 3/4" BI	G 3/4" BI
Aansluiting 2	G 3/4" BI	G 3/4" BI	G 3/4" BI	G 3/4" BI
Bevestigingsmethode	Handmatig	Handmatig	Handmatig	Handmatig
Totale gewicht	275 gram	595 gram	830 gram	830 gram
Totale lengte	1.500 mm	3.500 mm	5.000 mm	5.000 mm
Totale breedte	38 mm	38 mm	38 mm	38 mm
Totale hoogte	38 mm	38 mm	38 mm	38 mm
	Filling Hose	Filling Hose	Filling Hose	Filling Hose
	BASIC Blue incl. bleed key	BASIC Blue incl. bleed key	BASIC Blue incl. bleed key	BASIC Red incl. bleed key
	150 cm 3/4" F	350 cm 3/4" F	500 cm 3/4" F	500 cm 3/4" F
Material of the Hose	PVC	PVC	PVC	PVC
Material of the Coupling	POM	POM	POM	POM
Colour of the Hose	Blue	Blue	Blue	Red
Colour of the Coupling	White	White	White	White
Max. working temperature	25 °C	25 °C	25 °C	25 °C
Max. working pressure	10 bar	10 bar	10 bar	10 bar
Included accessory	Radiator bleed key	Radiator bleed key	Radiator bleed key	Radiator bleed key
Connection 1	G 3/4" F	G 3/4" F	G 3/4" F	G 3/4" F
Connection 2	G 3/4" F	G 3/4" F	G 3/4" F	G 3/4" F
Fastening method	Manual	Manual	Manual	Manual
Total weight	275 gram	595 gram	830 gram	830 gram
Total length	1.500 mm	3.500 mm	5.000 mm	5.000 mm
Total width	38 mm	38 mm	38 mm	38 mm
Total height	38 mm	38 mm	38 mm	38 mm