



	Vorstvrije Gevelkraan	Vorstvrije Gevelkraan	Vorstvrije Gevelkraan
	Chroom	Chroom	Zwart
	15 mm	22 mm	22 mm
Materiaal 1	Hpb 57-3	Hpb 57-3	Hpb 57-3
Materiaal 2	Roestvast Staal	Roestvast Staal	Roestvast Staal
Materiaal 3	Koper	Koper	Koper
Kleur	Chroom	Chroom	Mat Zwart
Oppervlaktebehandeling	Verchroomd (Gepolijst)	Verchroomd (Gepolijst)	Gepoedercoat
Min./max. werktemperatuur	-10/90 °C (piek 110 °C)	-10/90 °C (piek 110 °C)	-10/90 °C (piek 110 °C)
Max. werkdruk	10 bar	10 bar	10 bar
Inbegrepen accessoire	Kniekoppeling, Kraanstuk	Kniekoppeling, Kraanstuk	Kniekoppeling, Kraanstuk
Aansluiting 1	15 mm Koperen pijp	22 mm Koperen pijp	22 mm Koperen pijp
Aansluiting 2	G 3/4" BU	G 3/4" BU	G 3/4" BU
Bevestigingsmethode	Schroeven	Schroeven	Schroeven
Totale gewicht	590 gram	710 gram	720 gram
Totale lengte	515 mm	515 mm	515 mm
Totale breedte	80 mm	110 mm	110 mm
Totale hoogte	100 mm	110 mm	110 mm
	Frost-free Outside Tap	Frost-free Outside Tap	Frost-free Outside Tap
	Chrome	Chrome	Black
	15 mm	22 mm	22 mm
Material 1	Hpb 57-3	Hpb 57-3	Hpb 57-3
Material 2	Stainless Steel	Stainless Steel	Stainless Steel
Material 3	Copper	Copper	Copper
Colour	Chrome	Chrome	Matte Black
Surface finish	Chrome Plated (Polished)	Chrome Plated (Polished)	Powder Coated
Min./max. working temperature	-10/90 °C (peak 110 °C)	-10/90 °C (peak 110 °C)	-10/90 °C (peak 110 °C)
Max. working pressure	10 bar	10 bar	10 bar
Included accessory	Elbow Knee, Tap Piece	Elbow Knee, Tap Piece	Elbow Knee, Tap Piece
Connection 1	15 mm Copper pipe	22 mm Copper pipe	22 mm Copper pipe
Connection 2	G 3/4" M	G 3/4" M	G 3/4" M
Fastening method	Screws	Screws	Screws
Total weight	590 gram	710 gram	720 gram
Total length	515 mm	515 mm	515 mm
Total width	80 mm	110 mm	110 mm
Total height	100 mm	110 mm	110 mm