



	Vul- en Aftapkraan	Vul- en Aftapkraan	Vul- en Aftapkraan
	Chroom	Messing	Messing zonder hendel
	1/2"	1/2"	1/2"
Materiaal van het Huis	Hpb 57-3	Hpb 57-3	Hpb 57-3
Materiaal van de Hendel	Aluminium	Kunststof	N.V.T.
Kleur van het Huis	Zilverwit	Messing	Messing
Kleur van de Hendel	Rood	Rood	N.V.T.
Oppervlaktebehandeling	Vernikkeld (Gezandstraald)	N.V.T.	N.V.T.
Min./max. werktemperatuur	-10/90 °C (piek 110 °C)	-10/90 °C (piek 110 °C)	-10/90 °C (piek 110 °C)
Max. werkdruk	10 bar	10 bar	10 bar
Aansluiting 1	G 1/2" BU Zelfdichtend	R 1/2" BU	R 1/2" BU
Aansluiting 2	14-15 mm Tule	13-15 mm Tule	13-15 mm Tule
Aansluiting 3	G 3/4" BU	G 3/4" BU	G 3/4" BU
Bevestigingsmethode 1	22 mm Steeksleutel	24 mm Steeksleutel	24 mm Steeksleutel
Bevestigingsmethode 2	10 mm Inbus	10 mm Inbus	10 mm Inbus
Totale gewicht	155 gram	142 gram	138 gram
Totale lengte	73 mm	72 mm	72 mm
Totale breedte	30 mm	30 mm	30 mm
Totale hoogte	55 mm	47 mm	35 mm
	Fill and Drain Valve	Fill and Drain Valve	Fill and Drain Valve
	Chrome	Brass	Brass without handle
	1/2"	1/2"	1/2"
Material of the Body	Hpb 57-3	Hpb 57-3	Hpb 57-3
Material of the Handle	Aluminium	Plastic	N/A
Colour of the Body	Silvery-white	Brass	Brass
Colour of the Handle	Red	Red	N/A
Surface finish	Nickel Plated (Sandblasted)	N/A	N/A
Min./max. working temperature	-10/90 °C (peak 110 °C)	-10/90 °C (peak 110 °C)	-10/90 °C (peak 110 °C)
Max. working pressure	10 bar	10 bar	10 bar
Connection 1	G 1/2" M Self-sealing	R 1/2" M	R 1/2" M
Connection 2	14-15 mm Nozzle	13-15 mm Nozzle	13-15 mm Nozzle
Connection 3	G 3/4" M	G 3/4" M	G 3/4" M
Fastening method 1	22 mm Wrench	24 mm Wrench	24 mm Wrench
Fastening method 2	10 mm Allen Key	10 mm Allen Key	10 mm Allen Key
Total weight	155 gram	142 gram	138 gram
Total length	73 mm	72 mm	72 mm
Total width	30 mm	30 mm	30 mm
Total height	55 mm	47 mm	35 mm